



## **ENVIROALERT PROFESSIONAL®**

## **ENVIROALERT®**

Accessory for:

EnviroAlert EA200-12  
 EnviroAlert EA200-24  
 EnviroAlert EA400-12  
 EnviroAlert EA400-24  
 EnviroAlert EA800-ip  
 EnviroAlert Professional EAPro Gateway



### **Accessory for EnviroAlert consoles to monitor relative humidity**

- Maximum sensor cable run: 1,000' (305 m) [22 AWG twisted pair].
- Includes mounting screws and instruction manual.
- Wire not included.

For use in non-condensing environments such as an office or IT room. **NOT** for use in cooler or freezer.

### **Specifications**

Power Requirements	12 VDC @ 5mA
Sensing Range	5-95% RH ±5% @ 10-90% RH, 77° F (25°C)
Sensing Element	Capacitive / IC
Response Time	TC < 12 min
Operating Temperature	32° to 122° F (0° to 50° C)
Weight	5 oz (0.14 kg)
Dimensions	3 x 2 x 1.75" (7.6 x 5.08 x 4.45 cm)
Mounting	Surface mount

Visit [www.winland.com](http://www.winland.com), call 800.635.4269 or email [techsupport@winland.com](mailto:techsupport@winland.com) to learn more.



424 North Riverfront Drive, Suite 200 • Mankato, MN • 56001 • 800.635.4269 • [www.winland.com](http://www.winland.com)